




UP-1201 (2 Drum Spill Containment Deck)

- High-density polyethylene (HDPE) construction resists UV rays, rust, corrosion and most chemicals
- Ideal for 55-gallon sump
- Comply with EPA 40CFR 264.175, SPCC 40CFR112.7, EPA 40 CFR 122.26
- Low-profile 6" height makes load or unload easier
- Chemical Compatibility Strip equipped to test liquid adaptability with spill containment pallet
- Nestable design to minimize space for storage and shipment
- Build-in clips realize multiple decks combining to one drum storage platform
- Dual ends forklift pockets are compatible with most forklift trucks



Technical Data Sheet

Brand	UPQUARK
Model	UP-1201
Dimensions L x W x H cm (in.)	132 x 66 x 15 (52x26x6")
Color	Blue Grating/Yellow Deck
Material	High-Density Polyethylene (HDPE)
Weight kg (lb)	14 (31)
Sump Capacity Liters (gal)	80 (21)
Recommend Load Capacity (UDL) kg (lb)	1136 (2500)
Forklift Channels cm (in.)	Width 23.6 (9.3"), Inside Spread 33.3 (13.1"), Height 8.4 (3.3")
Regulation Standard	EPA 40CFR 264.175, SPCC 40CFR112.7, EPA 40 CFR 122.26
Style	Drum Spill Containment Pallets
Liquid Discharge Solution	Automatic Discharge Pump (UP-1999)

