



UPQUARK

Ningbo Sanyou Environmental Protection Technology Co., Ltd.



Tel : 86-13917455418
Whatsapp : 86-13917455418
Email: info@upquarksafety.com
Website:www.spillcontainmentpallet.com

UP-1206 (2 Drum Spill Containment Pallet Heavy Duty Model)

- High-density polyethylene (HDPE) construction resists UV rays, rust, corrosion and most chemicals
- 260 liters sump capacity can catch total leaks of one 55 gallons drums
- Comply with EPA 40CFR 264.175, SPCC 40CFR112.7, EPA 40 CFR 122.26, Oil storage regulation 2001
- Hot Dip Galvanized Steel Grating withstands extra-heavy loads
- Nestable design to minimize space for storage and shipment
- Interchangeable grating for easily leak detection and spills removing
- Chemical Compatibility Strip equipped to test liquid adaptability with spill containment pallet
- Dual ends forklift pockets are compatible with most forklift trucks



Technical Data Sheet

Brand	UPQUARK
Model	UP-1206
Dimensions L x W x H cm (in.)	132 x 66 x 43 (52x26x17")
Color	Hot Dip Galvanized Steel Grating/Yellow Pallet
Material	High-Density Polyethylene (HDPE)/Galvanized Steel
Weight kg(lb)	35(77)
Sump Capacity Liters (gal)	260 (69)
Recommend Load Capacity (UDL) kg (lb)	1363 (3005)
Forklift Channels cm (in.)	Width 31.7 (12.5"), Inside Spread 17.8 (7"), Height 10.8 (4.25")
Regulation Standard	EPA 40CFR 264.175, SPCC 40CFR112.7, EPA 40 CFR 122.26/Oil storage regulation 2001/PPG26
Style	Drum Spill Containment Pallets
Liquid Discharge Solution	Automatic Discharge Pump(UP-1999)



Technical Service:
technicalsupport@upquarksafety.com