

Ningbo Sanyou Environmental Protection Technology Co., Ltd.

NPDES (É defra

Tel: 86-13917455418 Whatsapp: 86-13917455418 Email: info@upquarksafety.com Website:www.spillcontainmentpallet.com

UP-1502 (IBC Spill Deck)

 High strength density polyethylene (HDPE) construction resists UV rays, rust, corrosion and most chemicals

EPA

SPC:

- > Ideal for 800, 1000 &1200 liters IBC tank
- Comply with EPA 40CFR 264.175, SPCC 40CFR112.7, NPDES 40 CFR 122.20
- > IBC can be loaded directly on the integral support columns
- > Cost effective design by eliminates grating
- Equipped with 1 fixator and 2 bulkhead flow-through connectors for pallets connection to expand sump capacity



Technical Data Sheet

Brand	UPQUARK
Model	UP-1502
Dimensions Lx W x H cm (in.)	140 x 117 x 24 (55x46x9.5")
Color	Yellow
Material	High Strength Density Polyethylene (HDPE)
Weight kg(lb)	27 (59.4)/each unit
Unit Sump Capacity liters (gal)	250 (66)/each unit
Recommend load capacity (UDL) kg (lb)	2500 (5500)/each unit
Regulation Standard	EPA 40CFR 264.175, SPCC 40CFR112.7, EPA 40 CFR 122.26
Style	IBC Spill Pallets
Liquid Discharge Solution	Pump



Technical Service: technicalsupport@upquarksafety.com