

UP-2201 (2 Drum Spill Containment Deck with Drain Plug)

- High-density polyethylene (HDPE) construction resists UV rays, rust, corrosion and most chemicals
- Applicable drum loading capacity to 55 gallons
- Comply with EPA 40CFR 264.175, SPCC 40CFR112.7, EPA 40 CFR 122.26
- Low-profile 5.9" height makes load or unload easier
- Fluorine rubber sealing ring in compliance with EN 14432
- 2 Sets of sealing plug & ring as replacing parts after drainage
- Nestable design to minimize the space for storage and shipment
- Dual ends forklift pockets are compatible with most forklift trucks



Technical Data Sheet

Brand	UPQUARK
Model	UP-2201
Dimensions L x W x H cm (in.)	130 x 68 x 15 (51.2x26.8x5.9")
Color	Black Grating/Yellow Deck
Material	High Density Polyethylene (HDPE)
Weight kg(lb)	15 (33)
Sump Capacity Liters (gal)	82 (21.7)
Recommend Load Capacity (UDL) kg (lb)	1500 (3300)
Regulation Standard	EPA 40CFR 264.175, SPCC 40CFR112.7, EPA 40 CFR 122.26
Style	Drum Spill Containment Pallets
Liquid Discharge Solution	Drain Plug

