

## Ningbo Sanyou Environmental Protection Technology Co., Ltd.













Tel: 86-13917455418 Whatsapp: 86-13917455418 Email: info@upquarksafety.com Website:www.spillcontainmentpallet.com

## **CER3M2450 (Hazmat Chemical Extremely Absorbent Rolls)**

- Applicable for most acids, alkalis, corrosives, chemicals and unknown liquids
- It is perfect for fast-flowing liquids or large-area spill containment
- Extremely technology realizes instant absorbing saturation in
- Unfolded roll fits floor well and can be placed under shelves or containers
- Tear able design for on site application to make cost effective spill containment solution
- Light-weight Level provides workshop economical spill containment solution
- Absorbent in high fiber construction leave no liquid or fiber residue



## **Technical Data Sheet**

Brand	UPQUARK
Model	CER3M2450
Fluid absorbed	Most hazmat chemical liquids
Dimensions cm (inch)	40x 5000 (16x2000")
Color	Yellow
Composition	Melt blown Polypropylene
Grammes per Square Metre	200gsm
Net Weight kg (pound)	4 (9)
Absorbency Duration	In seconds
Layer	3 layers, SMS
Absorbency Level	Light-weight Construction
Absorbency per Bag liter(gallon)	48 (13)
Absorbency per Roll liter(gallon)	48 (13)
Perforated Pattern cm (inch)	40x25 (16x10") sections
Sold as	1 Roll per Bag
Meets Regulations	29 CFR 1910.22(a)(2)

## Note:

- 1.Pls refer to local hazardous waste disposal methods after product application. Incineration is not recommended. Self-incineration may cause fire or produce toxic and harmful gases due to the decomposition of materials and adsorbed liquids.
- 2.PPE is compulsory for on-site personnel matching the hazard level of leaked chemical liquids.
- 3. Mixing of different saturated absorbent is prohibited in chemical-proof garbage bag.
- 4. Move and clean absorbed liquid asap.

