

## CR3M2745 (Hazmat Chemical Absorbent Rolls)

- Applicable for most acids, alkalis, corrosives, chemicals and unknown liquids
- It is perfect for fast-flowing liquids or large-area spill containment
- Unfolded roll fits floor well and can be placed under shelves or containers
- Tear able design for on site application to make cost effective spill containment solution
- Light-weight Level provides workshop economical spill containment solution
- Absorbent in high fiber construction leave no liquid or fiber residue
- Plastic packaging will not be ruined by water and self-extinguish with fire, which reduces fire flaming risk
- Optional Fluorescent sticker to the outer packaging for fast eye-catching in emergencies



## Technical Data Sheet

Brand	UPQUARK
Model	CR3M2745
Fluid absorbed	Most hazmat chemical liquids
Dimensions cm (inch)	76x 4572 (30x1800")
Color	Yellow
Composition	Melt blown Polypropylene
Grammes per Square Metre	200gsm
Net Weight kg (pound)	7 (15)
Absorbency Duration	About 15 seconds for most liquids
Layer	3 layers, SMS
Absorbency Level	Light-weight Construction
Absorbency per Bag liter(gallon)	84 (22)
Absorbency per Roll liter(gallon)	84 (22)
Perforated Pattern cm (inch)	38x25 (15x10") sections
Sold as	1 Roll per Plastic Box
Meets Regulations	29 CFR 1910.22(a)(2)

Note:

1. Pls refer to local hazardous waste disposal methods after product application. Incineration is not recommended. Self-incineration may cause fire or produce toxic and harmful gases due to the decomposition of materials and adsorbed liquids.
2. PPE is compulsory for on-site personnel matching the hazard level of leaked chemical liquids.
3. Mixing of different saturated absorbent is prohibited in chemical-proof garbage bag.
4. Move and clean absorbed liquid asap.



Technical Service:  
[technicalsupport@upquarksafety.com](mailto:technicalsupport@upquarksafety.com)