

Ningbo Sanyou Environmental Protection Technology Co., Ltd.











Tel: 86-13917455418 Whatsapp: 86-13917455418 Email: info@upquarksafety.com Website:www.spillcontainmentpallet.com

CSC7612 (Hazmat Absorbent Socks)

- Applicable for most acids, alkalis, corrosives, chemicals and unknown
- Ideal for mass chemical leakage soaking up and over spray containment in short time
- Soft long sock applicable in uneven surface or corner, applicable as blocking spill liquid around containers or corner as containing fence
- Polypropylene skin resists chemicals and tearing
- Plastic packaging will not be ruined by water and self-extinguish with fire
- Velcro seal eliminates sealing tape and realizes fast open-up
- Optional Fluorescent sticker to the outer packaging for fast eye-catching in emergencies
- Absorbent in high fiber construction leave no fiber residue
- Abrasion resistant Spun bond socks filled superfine melt blown polypropylene



Technical Data Sheet

Brand	UPQUARK
Model	CSC7612
Fluid absorbed	Most Hazmat chemical liquids
Dimensions cm (inch)	Ø7.6cmx1.2m(Ø3"x4')
Color	Yellow
Skin/Outer Mesh	Abrasion resistant Spun bond
Filler	Polypropylene
Net Weight kg (pound)	5.6 (12)
Application	Skimming
Absorbency per Box liter(gallon)	56 (15)
Absorbency per Sock liter(gallon)	3.5 (0.9)
Sold as	16 Socks per Plastic Box
Meets Regulations	29 CFR 1910.22(a)(2)
Absorbency per Sock liter(gallon) Sold as	3.5 (0.9) 16 Socks per Plastic Box

Note:

- 1. Pls refer to local hazardous waste disposal methods after product application. Incineration is not recommended. Self-incineration may cause fire or produce toxic and harmful gases due to the decomposition of materials and adsorbed liquids.
- 2. PPE is compulsory for on-site personnel matching the hazard level of leaked chemical liquids.
- 3. Mixing of different saturated absorbent is prohibited in chemical-proof garbage bag.
- 4. Move and clean absorbed liquid asap.

