

## Ningbo Sanyou Environmental Protection Technology Co., Ltd.













Tel: 86-13917455418 Whatsapp: 86-13917455418 Email: info@upquarksafety.com Website:www.spillcontainmentpallet.com

## CSC7636 (Hazmat Absorbent Socks)

- Applicable for most acids, alkalis, corrosives, chemicals and unknown
- Ideal for mass chemical leakage soaking up and over spray containment in short time
- Soft long sock applicable in uneven surface or corner, applicable as blocking spill liquid around containers or corner as containing fence
- Polypropylene skin resists chemicals and tearing
- Plastic packaging will not be ruined by water and self-extinguish with fire
- Velcro seal eliminates sealing tape and realizes fast open-up
- Optional Fluorescent sticker to the outer packaging for fast eye-catching in emergencies
- Absorbent in high fiber construction leave no fiber residue
- Abrasion resistant Spun bond socks filled superfine melt blown polypropylene



## **Technical Data Sheet**

Brand	UPQUARK
Model	CSC7636
Fluid absorbed	Most Hazmat chemical liquids
Dimensions cm (inch)	Ø7.6cmx3.6m(Ø3"x12')
Color	Yellow
Skin/Outer Mesh	Abrasion resistant Spun bond
Filler	Polypropylene
Net Weight kg (pound)	7.4 (16)
Application	Skimming
Absorbency per Box liter(gallon)	74 (20)
Absorbency per Sock liter(gallon)	10.6 (2.9)
Sold as	7 Socks per Plastic Box
Meets Regulations	29 CFR 1910.22(a)(2)

## Note:

- 1. Pls refer to local hazardous waste disposal methods after product application. Incineration is not recommended. Self-incineration may cause fire or produce toxic and harmful gases due to the decomposition of materials and adsorbed liquids.
- 2. PPE is compulsory for on-site personnel matching the hazard level of leaked chemical liquids.
- 3. Mixing of different saturated absorbent is prohibited in chemical-proof garbage bag.
- 4. Move and clean absorbed liquid asap.

