

Ningbo Sanyou Environmental Protection Technology Co., Ltd.













Tel: 86-13917455418 Whatsapp: 86-13917455418 Email: info@upquarksafety.com Website:www.spillcontainmentpallet.com

OP3M410 (Oil Only Sprint Absorbent Pads)

- It only absorbs oil-based liquids and hydrocarbons and repels all water
- Ideal for drips and soaking up spills containment
- Absorbing saturation achieved in 15 seconds for oil based liquid
- Plastic packaging will not be ruined by water and self-extinguish with
- Tear able design for on- site application to make cost effective spill containment solution
- Neat and dense dimple on absorbent surface enhance product strength
- Splash white color to catch oil & fuel leakage point after leakage in saturation level
- Heavyweight absorbent pad doubles sump capacity of light weight pad
- Absorbent in high fiber construction leave no fiber residue
- Optional Fluorescent sticker to the outer packaging for fast eye-catching in emergencies

Technical Data Sheet

Brand	UPQUARK
Model	OP3M410
Fluid absorbed	Oils, Fuels, Other Oil-Based Liquids Only
Dimensions cm (inch)	40x 50 (16x20")
Color	White
Composition	Melt blown Polypropylene
Grammes per Square Metre	400gsm
Net Weight kg (pound)	8 (18)
Absorbency Duration	About 15 seconds
Layer	3 layers, SMS
Absorbency Level	Heavy-weight Construction
Absorbency per Box liter(gallon)	133 (35)
Absorbency per Pad milliliter(ounce)	1330 (44)
Perforated Pattern cm (inch)	40x25 (16x10") sections
Sold as	100 Pads per Plastic Box
Meets Regulations	29 CFR 1910.22(a)(2), 40 CFR 112.7, 40 CFR 122.26

- 1. Cannot be used together with oil stain cleaning products such as degreasing agents.
- 2. Recyclable as disposal PP. Incineration is not recommended. Self-incineration may cause fire or produce toxic and harmful gases due to the decomposition of materials and adsorbed liquids.

