

Ningbo Sanyou Environmental Protection Technology Co., Ltd.

NPDES



Tel: 86-13917455418 Whatsapp: 86-13917455418 Email: info@upquarksafety.com Website:www.spillcontainmentpallet.com

OR3M2850 (Oil Only Sprint Absorbent Rolls)

- Ideal rolls for leaks soaking up and over spray containment \triangleright happened in large area
- It only absorbs oil-based liquids and hydrocarbons and repels all \geq water
- Absorbing saturation achieved in 15 seconds for oil based liquid \geq
- Unfolded roll fits floor well and can be placed under shelves or \geq machines
- \geq Tear able design for on site application to make cost effective spill containment solution
- Splash white color to catch oil & fuel leakage point after leakage \triangleright in saturation level
- Light-weight Level provides workshop economical spill containment solution \geq
- Absorbent in high fiber construction leave no liquid or fiber residue \triangleright
- Optional Fluorescent sticker to the outer packaging for fast eye-catching in emergencies \geq

Technical Data Sheet

Brand	UPQUARK
Model	OR3M2850
Fluid absorbed	Oils, Fuels, Other Oil-Based Liquids Only
Dimensions cm (inch)	80x 5000 (32x2000")
Color	White
Composition	Melt blown Polypropylene
Grammes per Square Metre	200gsm
Net Weight kg (pound)	8 (18)
Absorbency Duration	In seconds
Layer	3 layers, SMS
Absorbency Level	Light-weight Construction
Absorbency per Bag liter(gallon)	133 (35)
Absorbency per Roll liter(gallon)	133 (35)
Perforated Pattern cm (inch)	40x25 (16x10") sections
Sold as	1 Roll per Bag
Meets Regulations	29 CFR 1910.22(a)(2)



Note:

1. Cannot be used together with oil stain cleaning products such as degreasing agents.

2. Recyclable as disposal PP. Incineration is not recommended. Self-incineration may cause fire or produce toxic and harmful gases due to the decomposition of materials and adsorbed liquids.



Technical Service: technicalsupport@upquarksafety.com