

OR3M3745 (Oil Only Sprint Absorbent Rolls)

- Ideal rolls for leaks soaking up and over spray containment happened in large area
- It only absorbs oil-based liquids and hydrocarbons and repels all water
- Absorbing saturation achieved in 15 seconds for oil based liquid
- Unfolded roll fits floor well and can be placed under shelves or machines
- Tear able design for on site application to make cost effective spill containment solution
- Splash white color to catch oil & fuel leakage point after leakage in saturation level
- Mid-weight absorbent pad applies to both small leakage and to large spill
- Absorbent in high fiber construction leave no liquid or fiber residue
- Optional Fluorescent sticker to the outer packaging for fast eye-catching in emergencies



Technical Data Sheet

| | |
|-----------------------------------|---|
| Brand | UPQUARK |
| Model | OR3M3745 |
| Fluid absorbed | Oils, Fuels, Other Oil-Based Liquids Only |
| Dimensions cm (inch) | 76x 4572 (30x1800") |
| Color | White |
| Composition | Melt blown Polypropylene |
| Grammes per Square Metre | 300gsm |
| Net Weight kg (pound) | 10 (23) |
| Absorbency Duration | About 15 seconds |
| Layer | 3 layers, SMS |
| Absorbency Level | Mid-weight Construction |
| Absorbency per Bag liter(gallon) | 173 (46) |
| Absorbency per Roll liter(gallon) | 173 (46) |
| Perforated Pattern cm (inch) | 40x25 (16x10") sections |
| Sold as | 1 Roll per Bag |
| Meets Regulations | 29 CFR 1910.22(a)(2) |

Note:

1. Cannot be used together with oil stain cleaning products such as degreasing agents.
2. Recyclable as disposal PP. Incineration is not recommended. Self-incineration may cause fire or produce toxic and harmful gases due to the decomposition of materials and adsorbed liquids.



Technical Service:
technicalsupport@upquarksafety.com