

## OR3M4450 (Oil Only Sprint Absorbent Rolls)

- Ideal rolls for leaks soaking up and over spray containment happened in large area
- It only absorbs oil-based liquids and hydrocarbons and repels all water
- Absorbing saturation achieved in 15 seconds for oil based liquid
- Unfolded roll fits floor well and can be placed under shelves or machines
- Tear able design for on site application to make cost effective spill containment solution
- Splash white color to catch oil & fuel leakage point after leakage in saturation level
- Heavyweight absorbent roll doubles sump capacity of light weight roll
- Absorbent in high fiber construction leave no liquid or fiber residue
- Optional Fluorescent sticker to the outer packaging for fast eye-catching in emergencies



## Technical Data Sheet

Brand	UPQUARK
Model	OR3M4450
Fluid absorbed	Oils, Fuels, Other Oil-Based Liquids Only
Dimensions cm (inch)	40x 5000 (16x2000")
Color	White
Composition	Melt blown Polypropylene
Grammes per Square Metre	400gsm
Net Weight kg (pound)	8 (18)
Absorbency Duration	About 15 seconds
Layer	3 layers, SMS
Absorbency Level	Heavy-weight Construction
Absorbency per Bag liter(gallon)	133 (35)
Absorbency per Roll liter(gallon)	133 (35)
Perforated Pattern cm (inch)	40x25 (16x10") sections
Sold as	1 Roll per Bag
Meets Regulations	29 CFR 1910.22(a)(2)

Note:

1. Cannot be used together with oil stain cleaning products such as degreasing agents.
2. Recyclable as disposal PP. Incineration is not recommended. Self-incineration may cause fire or produce toxic and harmful gases due to the decomposition of materials and adsorbed liquids.



**Technical Service:**  
[technicalsupport@upquarksafety.com](mailto:technicalsupport@upquarksafety.com)