Ningbo Sanyou Environmental Protection Technology Co., Ltd.













Tel: 86-13917455418 Whatsapp: 86-13917455418 Email: info@upquarksafety.com Website:www.spillcontainmentpallet.com

OR3M4850 (Oil Only Sprint Absorbent Rolls)

- Ideal rolls for leaks soaking up and over spray containment happened in large area
- It only absorbs oil-based liquids and hydrocarbons and repels all water
- Absorbing saturation achieved in 15 seconds for oil based liquid
- Unfolded roll fits floor well and can be placed under shelves or
- Tear able design for on site application to make cost effective spill containment solution
- Splash white color to catch oil & fuel leakage point after leakage in saturation level
- Heavyweight absorbent roll doubles sump capacity of light weight roll
- Absorbent in high fiber construction leave no liquid or fiber residue
- Optional Fluorescent sticker to the outer packaging for fast eye-catching in emergencies

Technical Data Sheet

Brand	UPQUARK
Model	OR3M4850
Fluid absorbed	Oils, Fuels, Other Oil-Based Liquids Only
Dimensions cm (inch)	80x 5000 (32x2000")
Color	White
Composition	Melt blown Polypropylene
Grammes per Square Metre	400gsm
Net Weight kg (pound)	16 (35)
Absorbency Duration	About 15 seconds
Layer	3 layers, SMS
Absorbency Level	Heavy-weight Construction
Absorbency per Bag liter(gallon)	266 (70)
Absorbency per Roll liter(gallon)	266 (70)
Perforated Pattern cm (inch)	40x25 (16x10") sections
Sold as	1 Roll per Bag
Meets Regulations	29 CFR 1910.22(a)(2)



Note:

- 1. Cannot be used together with oil stain cleaning products such as degreasing agents.
- 2. Recyclable as disposal PP. Incineration is not recommended. Self-incineration may cause fire or produce toxic and harmful gases due to the decomposition of materials and adsorbed liquids.

