

UER3M4450 (Universal Extremely Absorbent Rolls)

- It is perfect for fast-flowing liquids or large-area spill containment
- Extremely technology realizes instant absorbing saturation in seconds
- Absorbs most industrial liquids including but not limit to oils, water, solvents, coolants and more
- Unfolded roll fits floor well and can be placed under shelves or machines
- Tear able design for on site application to make cost effective spill containment solution
- Heavyweight absorbent roll doubles sump capacity of light weight roll
- Absorbent in high fiber construction leave no liquid or fiber residue



Technical Data Sheet

Brand	UPQUARK
Model	UER3M4450
Fluid absorbed	Most industrial liquids
Dimensions cm (inch)	40x 5000 (16x2000")
Color	Gray
Composition	Melt blown Polypropylene
Grammes per Square Metre	400gsm
Net Weight kg (pound)	8 (18)
Absorbency Duration	In seconds
Layer	3 layers, SMS
Absorbency Level	Heavy-weight Construction
Absorbency per Bag liter(gallon)	96 (25)
Absorbency per Roll liter(gallon)	96 (25)
Perforated Pattern cm (inch)	40x25 (16x10") sections
Sold as	1 Roll per Bag
Meets Regulations	29 CFR 1910.22(a)(2)

Note:

1. Not recommended to use for toxic, harmful, corrosive liquids unless this product is the only one in hand when a chemical liquid leaks. Please refer to the article for specific reasons.
2. Recyclable as disposal PP. Incineration is not recommended. Self-incineration may cause fire or produce toxic and harmful gases due to the decomposition of materials and adsorbed liquids.



Technical Service:
technicalsupport@upquarksafety.com