

UP3M410 (Universal Absorbent Pads)

- It soaks up oil, coolants, solvents and water-based fluids anywhere in your facility
- Catch up spill liquid in short time to avoid pollution spray
- Plastic packaging will not be ruined by water and self-extinguish with fire
- Tear able design for on- site application to make cost effective spill containment solution
- Neat and dense dimple on absorbent surface enhance product strength
- Heavyweight absorbent pad doubles sump capacity of light weight pad
- Absorbent in high fiber construction leave no fiber residue
- Optional Fluorescent sticker to the outer packaging for fast eye-catching in emergencies



Technical Data Sheet

Brand	UPQUARK
Model	UP3M410
Fluid absorbed	Most industrial liquids
Dimensions cm (inch)	40x 50 (16x20")
Color	Gray
Composition	Melt blown Polypropylene
Grammes per Square Metre	400gsm
Net Weight kg (pound)	8 (18)
Absorbency Duration	About 15 seconds for most liquids
Layer	3 layers, SMS
Absorbency Level	Heavy-weight Construction
Absorbency per Box liter(gallon)	96 (25)
Absorbency per Pad milliliter(ounce)	960 (32)
Perforated Pattern cm (inch)	40x25 (16x10") sections
Sold as	100 Pads per Plastic Box
Meets Regulations	29 CFR 1910.22(a)(2)

Note:

1. Not recommended to use for toxic, harmful, corrosive liquids unless this product is the only one in hand when a chemical liquid leaks. Please refer to the article for specific reasons.
2. Recyclable as disposal PP. Incineration is not recommended. Self-incineration may cause fire or produce toxic and harmful gases due to the decomposition of materials and adsorbed liquids.



Technical Service:
technicalsupport@upquarksafety.com