# Ningbo Sanyou Environmental Protection Technology Co., Ltd.













Tel: 86-13917455418 Whatsapp: 86-13917455418 Email: info@upquarksafety.com Website:www.spillcontainmentpallet.com

## **UR3M3850 (Universal Absorbent Rolls)**

- It is perfect for fast-flowing liquids or large-area spill containment
- Absorbs most industrial liquids including but not limit to oils, water, solvents, coolants and more
- Catch up spill liquid in short time to avoid pollution spray
- Unfolded roll fits floor well and can be placed under shelves or machines
- Tear able design for on site application to make cost effective spill containment solution
- Plastic packaging will not be ruined by water and self-extinguish with fire
- Mid-weight absorbent pad applies to both small leakage and to
- Absorbent in high fiber construction leave no liquid or fiber residue
- Optional Fluorescent sticker to the outer packaging for fast eye-catching in emergencies

### **Technical Data Sheet**

Brand	UPQUARK
Model	UR3M3850
Fluid absorbed	Most industrial liquids
Dimensions cm (inch)	80x 5000 (32x2000")
Color	Gray
Composition	Melt blown Polypropylene
Grammes per Square Metre	300gsm
Net Weight kg (pound)	12 (26)
Absorbency Duration	About 15 seconds for most liquids
Layer	3 layers, SMS
Absorbency Level	Mid-weight Construction
Absorbency per Bag liter(gallon)	144 (38)
Absorbency per Roll liter(gallon)	144 (38)
Perforated Pattern cm (inch)	40x25 (16x10") sections
Sold as	1 Roll per Plastic Box
Meets Regulations	29 CFR 1910.22(a)(2)



#### Note:

- 1. Not recommended to use for toxic, harmful, corrosive liquids unless this product is the only one in hand when a chemical liquid leaks. Please refer to the article for specific reasons.
- 2. Recyclable as disposal PP. Incineration is not recommended. Self-incineration may cause fire or produce toxic and harmful gases due to the decomposition of materials and adsorbed liquids.

