

Ningbo Sanyou Environmental Protection Technology Co., Ltd.













Tel: 86-13917455418 Whatsapp: 86-13917455418 Email: info@upquarksafety.com Website:www.spillcontainmentpallet.com

OB206 (Oil Absorbent Boom)

- Widely used in spill containment in port, oil container storage & petroleum tank transportation industry
- It only absorbs oil-based liquids and hydrocarbons and repels all water
- Blocking & absorbing floating oil & oil based liquid as well as cleaning oil spill on water
- \triangleright Bright white color for easy eye catching in outdoor environments and clearly shows saturation level
- Abrasion resistant Spun bond socks filled superfine melt blown polypropylene
- Strong, zinc-plated carbon steel clips and rings to realize booms connection & extension
- Absorbent in high fiber construction leave no fiber residue
- Flame retardant and self-extinguishing melt-blown polypropylene reduces fire risk and extend durability

Technical Data Sheet

Brand	UPQUARK
Model	OB206
Fluid absorbed	Oils, Fuels, Other Oil-Based Liquids Only
Dimensions cm (inch)	Ø20cm x 6m (Ø8" x 20')
Color	White
Skin/Outer Mesh	Abrasion resistant Spun bond
Filler	Polypropylene
Net Weight kg (pound)	16 (35)
Application	Skimming
Absorbency per Bag liter(gallon)	213 (56)
Absorbency per Sock liter(gallon)	106 (28)
Sold as	2 Booms per Bag
Meets Regulations	40 CFR 112.7, 40 CFR 122.26



Note:

- 1. Cannot be used together with oil stain cleaning products such as degreasing agents.
- 2. Recyclable as disposal PP. Incineration is not recommended. Self-incineration may cause fire or produce toxic and harmful gases due to the decomposition of materials and adsorbed liquids.

