

Ningbo Sanyou Environmental Protection Technology Co., Ltd.













Tel : 86-13917455418 Whatsapp : 86-13917455418 Email: info@upquarksafety.com

UP-1501 (Single IBC Bund)

- High strength density polyethylene (HDPE) construction resists
 UV rays, rust, corrosion and most chemicals
- Ideal for 1000 liters or 1200 liters IBC tank loading
- Comply with EPA 40CFR 264.175, SPCC 40CFR112.7, EPA 40 CFR 122.26, Oil storage regulation 2001
- 12 Integral columns design ensures stable & excellent load capacity
- Costing effective by removing grating
- Nestable design to minimal the space for storage and shipment
- Dual ends forklift pockets are compatible with most forklift trucks



Technical Data Sheet

Brand	UPQUARK
Model	UP-1501
Dimensions L x W x H cm (in.)	165 x 155 x 71.5 (65x61x28")
Color	Yellow
Material	High Strength Density Polyethylene (HDPE)
Weight kg(lb)	65 (143)
Sump Capacity liters (gal)	1100 (291)
Recommend load capacity (UDL) kg (lb)	1500 (3307)
Forklift Channels cm (in.)	Width 24.5 (9.6"), Inside Spread 14.5 (5.7"), Height 10.0 (3.9")
Regulation Standard	EPA 40CFR 264.175, SPCC 40CFR112.7, EPA 40 CFR 122.26
Style	IBC Spill Pallets
Liquid Discharge Solution	Automatic Discharge Pump(UP-1999)



Technical Service: technical Support@upquarksafety.com