

Ningbo Sanyou Environmental Protection Technology Co., Ltd.

NPDES (C defra Approv

Tel: 86-13917455418 Whatsapp: 86-13917455418 Email: info@upquarksafety.com Website:www.spillcontainmentpallet.com

UP-1503 (10 Drum Spill Pallet)

 Linear low density polyethylene (LLDPE) construction resists UV rays, rust, corrosion and most chemicals

SPC

- Ideal for 10 ea 55 gallon drums' storage & spill containment
- Comply with EPA 40CFR 264.175, SPCC 40CFR112.7
 EPA 40 CFR 122.26, Oil storage regulation 2001
- > 46cm height for easy step up without ladder
- Slipping-preventing grating for safely operation on spill pallet
- Nestable design to minimize space for storage and shipment



> Dual ends forklift pockets are compatible with most forklift trucks

Technical Data Sheet

Brand	UPQUARK
Model	UP-1503
Dimensions L x W x H cm (in.)	340 x 160 x 46 (134x63x18")
Color	Yellow Pallet/Black Gratings
Material	Linear low density polyethylene (LLDPE)
Weight kg(lb)	158 (348)
Sump Capacity liters (gal)	1600 (422)
Recommend load capacity (UDL) kg (lb)	4500 (9920)
Forklift Channels cm (in.)	Width 24.5 (9.6"), Inside Spread 14.5 (5.7"), Height 10.0
Regulation Standard	EPA 40CFR 264.175, SPCC 40CFR112.7, EPA 40 CFR 122.26, Oil storage regulation 2001,PPG26
Style	Drum Spill Containment Pallets
Liquid Discharge Solution	Automatic Discharge Pump(UP-1999)



Technical Service: technicalsupport@upquarksafety.com