



UPQUARK

Ningbo Sanyou Environmental Protection Technology Co., Ltd.



Tel : 86-13917455418
Whatsapp : 86-13917455418
Email: info@upquarksafety.com
Website:www.spillcontainmentpallet.com

UP-1503 (Triple IBC Spill Pallet)

- Linear low density polyethylene (LLDPE) construction resists UV rays, rust, corrosion and most chemicals
- Ideal for 3 ea IBC tanks loading
- Comply with EPA 40CFR 264.175, SPCC 40CFR112.7 EPA 40 CFR 122.26, Oil storage regulation 2001, PPG26
- 46cm height for easy step up without ladder
- Slipping- prevention grating design for operation on IBC pallet
- Nestable design to minimize space for storage and shipment
- Dual ends forklift pockets are compatible with most forklift trucks



Technical Data Sheet

Brand	UPQUARK
Model	UP-1503
Dimensions Lx W x H cm (in.)	340 x 160 x 46 (134x63x18")
Color	Yellow Pallet/Black Gratings
Material	Linear low density polyethylene (LLDPE)
Weight kg(lb)	158 (348)
Sump Capacity liters (gal)	1600 (422)
Recommend load capacity (UDL) kg (lb)	4500 (9920)
Forklift Channels cm (in.)	Width 24.5 (9.6"), Inside Spread 14.5 (5.7"), Height 10.0
Regulation Standard	EPA 40CFR 264.175, SPCC 40CFR112.7, EPA 40 CFR 122.26, Oil storage regulation 2001, PPG26
Style	IBC Spill Pallets
Liquid Discharge Solution	Automatic Discharge Pump(UP-1999)



Technical Service:
technicalsupport@upquarksafety.com