

UP-412811 (2 Drum Mobile Steel Spill Pallet)

- Sturdy, double layers steel constructions, Powder coated and Hot-dip galvanized surface in 3mm Steel sheet
- Ideal for to 55 gallons capacity drum
- Mobile pallet for flexible application of spill control
- Applicable for flammable liquids in GHS categories 1-3 as well as hazardous liquids in GHS categories 1-4
- Removable zinc plated grating, Max load 1000 kg/m²
- Optional fastener for drum and pallet fixing
- Recommended load capacity 440kg



Technical Data Sheet

Brand	UPQUARK
Model	UP-412811
Dimensions LxWxH cm (in.)	120x80x111.5 (47.24x31.5x43.9")
Color	Blue/Yellow/Orange/Hot Dip Galvanized
Material	Surface powder coat and hot-dip galvanized steel
Weight kg(lb)	90 (198)
Sump Capacity Liters (gal)	215 (57)
Recommend Load Capacity (UDL) kg (lb)	440 (970)
Regulation Standard	EPA 40CFR 264.175, SPCC 40CFR112.7, EPA 40 CFR 122.26
Style	Steel Spill Pallet
Liquid Discharge Solution	Automatic Discharge Pump(TWK-1999)
Fixing Strap for Two Drums	1 set (UP-1997)

