



UPQUARK

Ningbo Sanyou Environmental Protection Technology Co., Ltd.



Tel : 86-13917455418
Whatsapp : 86-13917455418
Email: info@upquarksafety.com
Website:www.spillcontainmentpallet.com

UP-426134 (6 Drum Steel Spill Pallet)

- Sturdy, double layers steel constructions, Powder coated and Hot-dip galvanized surface in 3mm Steel sheet
- Ideal for to 55 gallons drum
- Applicable for flammable liquids in GHS categories 1-3 as well as hazardous liquids in GHS categories 1-4
- Sump clearance height 100mm, easy for hoisting and transportation
- Recommend load capacity 3800kg



Technical Data Sheet

Brand	UPQUARK
Model	UP-426134
Dimensions L x W x H cm (in.)	265x130x43.5 (104.33x51.18x17.13")
Color	Blue/Yellow/Orange/Hot Dip Galvanized
Material	Surface powder coat and hot-dip galvanized steel
Weight kg(lb)	250 (551)
Sump Capacity Liters (gal)	1400 (369)
Recommend Load Capacity (UDL) kg (lb)	3800 (8377)
Regulation Standard	EPA 40CFR 264.175, SPCC 40CFR112.7, EPA 40 CFR 122.26, Oil storage regulation 2001
Style	Drum Spill Containment Pallets
Liquid Discharge Solution	Automatic Discharge Pump(UP-1999)



Technical Service:
technicalsupport@upquarksafety.com